Section 1: Identification

PRODUCT NAME: Southern Yellow Pine Plywood

SYNONYMS: SYP plywood; plywood

CHEMICAL NAME/FAMILY: Wood Products

Manufacturer's Name: Hunt Forest Products, LLC Business Phone: (318) 255-2245

Address: 401 Reynolds Drive FAX: (318) 255-4048

Ruston, LA 71270

Section 2: Hazard(s) Identification

This product does not present hazards requiring the preparation of a Safety Data Sheet unless it is utilized in a manner that creates wood dust. Any manual or mechanical cutting or abrasion process performed on this product may create particles of **wood dust**. This **wood dust** and the product itself may exhibit certain health or physical hazards as described in this Safety Data Sheet.

PHYSICAL HAZARDS: Product or material may form dust concentrations in air during processing that may

be combustible when exposed to an ignition source (combustible dust).

HEALTH HAZARDS: Wood dust may cause nasopharyngeal cancer and/or cancer of the nasal cavities

and paranasal sinuses.

SIGNAL WORD(S): DANGER

Health Hazard: 1 Flammability Hazard: 1 Reactivity Hazard: 0

Hazard(s) not otherwise classified (HNOC): None

PRECAUTIONARY STATEMENTS:

Prevention: Do not handle until all safety precautions have been read and understood. Wear

eye and respiratory protection for excessive wood dust exposures. Do not breathe dust. In case of inadequate ventilation, wear respiratory protection. Avoid dust

accumulation to minimize explosion hazard.

Response: If exposed or concerned, get medical advice/attention. Remove contact lenses if

present and rinse eyes thoroughly if particles are in the eye. If eye irritation

persists, get medical advice/attention. In case of fire, use CO2, foam or water spray.

Page 1 of 9

Section 3: Composition/Information on Ingredients

PRINCIPAL HAZARDOUS COMPONENTS (Chemical and common names):

Wood/Wood Dust CAS# N/A 95-97%Phenol Formaldehyde Resin 9003-35-4 3-5%

Section 4: First-Aid Measures

Inhalation: Remove to fresh air. Seek medical attention if persistent irritation, severe coughing or

breathing difficulty occurs.

Skin Contact: Wood dust of certain species may cause allergic contact dermatitis in sensitized individuals.

Wash affected skin with mild soap and water. Seek medical attention if rash, irritation or

dermatitis persists.

Eyes: Wood dust may cause physical irritation. Flush eyes with water to remove particles. If eye

irritation persists, seek medical attention.

Ingestion: Rinse mouth if ingestion occurs. Seek medical attention if discomfort persists.

Health Effects: ACUTE: Wood dust can cause eye, skin and respiratory irritation.

CHRONIC: Wood dust may cause allergic contact dermatitis and respiratory sensitivity

with prolonged, repetitive contact or exposure to elevated dust

concentrations. Wood dust may cause nasopharyngeal cancer and/or

cancer of the nasal cavities and paranasal sinuses.

Section 5: Fire-Fighting Measures

Extinguishing Media: Water, foam, dry chemical, carbon dioxide, sand.

Special Fire Fighting Procedures: None.

Unusual Fire and Explosion Hazards: Depending on moisture content, and more importantly, particle diameter and airborne concentration, wood dust may explode in the presence of an ignition source. An airborne concentration of 40 grams (40,000 mg) of dust per cubic meter of air is often used as the LEL for wood dusts. Reference NFPA Standards 654 and 664 for guidance. Ventilation systems should be kept clean and precautions should be taken to prevent sparks or other ignition sources.

Section 6: Accidental Release Measures

Steps to be taken in case material is released or spilled: Sweep or vacuum up for recovery and disposal. Avoid creating dusty conditions whenever feasible. Maintain good housekeeping to avoid accumulation of wood dust on exposed surfaces. Use approved filtering facepiece respirator (dust mask) and goggles where ventilation is not possible and exposure limits may be exceeded, or for additional worker comfort.

Section 7: Handling and Storage

Precautions for Safe Handling: Dried wood dust may represent a combustible dust hazard. Keep away from ignition sources. Avoid eye contact. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of wood dust. Store in well-ventilated, cool, dry place away from open flame.

Section 8: Exposure Controls/Personal Protection

Occupational Exposure Limits:

Component(s)	Type	Exposure Limit(s)	<u>Comments</u>
Wood Dust	PEL	5 mg/m3	Respirable dust ¹
	PEL	15 mg/m3	Total dust ¹
	TWA	1 mg/m3	Inhalable fraction

¹In AFL-CIO v OSHA, 965965 F. 2d 962 (11th Cir. 1992), the court overturned OSHA's 1989 Air Contaminants Rule, including the specific PELs for wood dust that OSHA had established at that time. The 1989 PELs were: TWA - 5.0 mg/m³; STEL (15 min.) - 10.0 mg/m³ (All soft and hard woods, except western red cedar); Western red cedar: TWA - 2.5 mg/m³.

Wood dust is now officially regulated as an organic dust under the Particulates Not Otherwise Regulated (PNOR) or Inert or Nuisance Dust categories as PELs noted under Health Effects Information section of this SDS. However, a number of states have incorporated provisions of the 1989 standard in their state plans. Additionally, OSHA has announced that it may cite companies under the OSH Act general duty clause under appropriate circumstances for non-compliance with the 1989 PELs.

Respiratory Protection: Use NIOSH approved filtering face piece respirator (dust mask) or higher levels of

respiratory protection as required if there is a potential to exceed the exposure

limits, or for symptom relief or worker comfort.

Ventilation: Local exhaust preferred. Provide so that exposure limits are met. Ventilation to control

dust should be considered where potential explosive concentrations and ignition sources are present. The design and operation of any ventilation system should consider the

possibility of explosive concentrations of wood dust within the system.

Protective Gloves: Leather or fabric gloves.

Eye Protection: Safety goggles or safety glasses to prevent eye contact where exposure to excessive

wood dust may occur.

Skin Protection: To prevent repeated or prolonged skin contact, clothing which covers the arms is

recommended.

Work/Hygiene Practices: Follow good hygienic and housekeeping practices. Clean up areas where

wood dust settles to avoid excessive accumulation of dust in order to minimize explosion hazard. Minimize compressed air blowdown or other

practices which generate high airborne-dust concentrations.

Section 9: Physical and Chemical Properties

Appearance: Light to dark colored, granular solid. Color dependent upon age and weathering.

Odor: Mild (slight pine odor)

Odor Threshold: N/A
Vapor Pressure: N/A
Vapor Density: N/A
pH: N/A
Relative Density g/cc: N/A

Flammability Limits: Upper Explosion Limit – N/A; Lower Explosion Limit – 40 g/m³

Autoignition Temperature: 400–500°F (204–260°C)

Decomposition Temperature: N/A

Melting Point: N/A

Freezing Point: N/A

Initial Boiling Point: N/A

Flash Point: N/A

Water Solubility: Insoluble

Evaporation Rate: N/A

Partition coefficient (n-octanol/water): N/A

Viscosity cps: N/A
Percent Volatile by Volume: N/A

Section 10: Stability and Reactivity

Reactivity: None.

Chemical Stability: Compound is stable under normal ambient temperature and conditions while in

storage and being handled. Explosion may occur when dust is present in air at high concentrations and exposed to excessive heat, sparks or open flames.

Incompatibility: Avoid contact with oxidizing agents and drying oils.

Hazardous polymerization: Will not occur.

Hazardous Decomposition Products: Thermal decomposition may yield carbon dioxide and/or carbon monoxide, nitrogen oxides, terpenes and polycyclic aromatic compounds. Natural decomposition of organic materials such as wood may produce toxic gases and an oxygen deficient atmosphere in enclosed or poorly ventilated areas. Spontaneous and rapid hazardous decomposition will not occur.

Section 11: Toxicological Information

Information on likely routes of exposure:

Inhalation: Airborne treated or untreated wood may cause nose, throat, or lung

irritation and other respiratory effects. Breathing excessive amounts of wood dust (primarily hardwood) has been associated with nasal cancer in some industries. Various species of untreated wood dust can elicit allergic

respiratory response in sensitized persons.

Skin contact: Handling may cause splinters. Dust may irritate skin. Some wood species

may cause allergic dermatitis in certain individuals.

Eye contact: Dust may irritate the eyes.

Ingestion: Not likely, due to the form of the product. However, ingestion of dusts

generated during working operations may cause nausea and vomiting.

Symptoms related to the physical, chemical and

toxicological characteristics

Wood dust: May cause nasal dryness, irritation and mucostasis. Coughing, wheezing, sneezing, sinusitis and prolonged colds have also been reported. Depending on wood species, may cause respiratory sensitization and/or irritation. Dust may cause eye, skin, and respiratory tract irritation.

Symptoms can include irritation, redness, scratching of the cornea, and

tearing. May cause nasal dryness, irritation, and mucostasis. Coughing, wheezing, sneezing, sinusitis. May cause eczema-like skin disorders (dermatitis). Airborne treated or untreated wood dust may cause nose, throat, or lung irritation and other respiratory effects.

Information on toxicological effects:

Acute toxicity Not expected to be acutely toxic.

Skin corrosion/irritation Dust may irritate skin.

Serious eye damage/eye

irritation

Dust may irritate eyes.

Respiratory or skin sensitization:

Respiratory sensitization Exposure to wood dusts can result in hypersensitivity.

Skin sensitization Exposure to wood dust can result in the development of contact

dermatitis. The primary irritant dermatitis resulting from skin contact with wood dusts consists of erythema, blistering, and

sometimes erosion and secondary infections occur.

Germ cell mutagenicity No component of this product presents at levels greater than or

equal to 0.1% is identified as a mutagen by OSHA.

Carcinogenicity May cause cancer by inhalation.

Untreated wood dust or saw dust: The International Agency for Research on Cancer (IARC) classifies untreated wood dust as a Group I human carcinogen. The classification is based primarily on IARC 's evaluation of increased risk in the occurrence of adenocarcinomas of the nasal cavities and paranasal sinuses associated with occupational exposures of untreated wood dust. Epidemiological studies have been reported on carcinogenic risks of employment in the furniture-making industry, the carpentry industry, and the lumber and sawmill industry. IARC has reviewed these studies and reports that there is sufficient evidence that nasal carcinomas have been caused by

employment in the furniture-making industry where the excess risk is associated with exposure to untreated wood dust or sawdust from hardwood species. IARC concluded that epidemiological data are not sufficient to make a definite assessment of the carcinogenic risk of employment as a carpenter or worker in a lumber mill or sawmill.

IARC Mongraphs. Overall Evaluation of Carcinogenicity

Wood Dust (CAS N/A) 1 Carcinogenic to humans.

NRP Report on Carcinogens

Wood Dust (CAS N/A) Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental

effects.

Specific target organ toxicity

single exposure

Not classified.

Specific target organ toxicity

repeated exposure

Not classified.

Aspiration hazard Not likely, due to the form of the product.

Chronic effects Chronic exposure to wood dusts can result in pneumonitis, and coughing,

wheezing, fever and the other signs and symptoms associated with chronic

bronchitis.

Section 12: Ecological Information

Ecotoxicity: None known.

Biopersistance and Degradability: Wood naturally decomposes and is biodegradable.

Bioaccumulation: Not expected to occur.

Soil Mobility: N/A

Other Adverse Effects: None known.

Section 13: Disposal Considerations

Disposal Instructions: Incinerate under safe conditions or landfill. Dispose of in accordance with

local, State and Federal regulations.

Page 7 of 9

Section 14: Transport Information

SHIPPING DESCRIPTION: Not Regulated under DOT DOT PROPER SHIPPING NAME: Not Regulated under DOT

UN/NA NUMBER: N/A
DOT HAZARD CLASS: N/A
PACKING GROUP: N/A

Section 15: Regulatory Information

SARA TITLE III INFORMATION

ComponentEHS RQ (LBS)EHS TPQ (LBS)Section 313 (Y/N)311/312 CategoriesWood DustN/AN/ANAcute/Chronic

TSCA: Not regulated.

CERCLA: Not regulated.

OSHA: Wood dust is a "hazardous chemical".

US State Regulations:

California Proposition 65 – Warning: Drilling, sawing, sanding or machining wood products generates wood dust, a substance known to the State of California to cause cancer.

Pennsylvania: Wood dust appears on Pennsylvania's Appendix A, Hazardous Substance List.

New Jersey: Wood dust appears on New Jersey's Hazardous Substance List.

WHMIS Classification: Controlled Product: D2A – wood dust: IARC Group 1.

Section 16: Other Information

The data in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

Some of the information presented here and conclusions drawn are from sources other than direct test data in the product itself.

THE INFORMATION AND DATA CONTAINED HEREIN ARE BELIEVED TO BE ACCURATE AND HAVE BEEN COMPILED FROM SOURCES BELIEVED TO BE RELIABLE. HUNT FOREST PRODUCTS MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, CONCERNING THE COMPLETENESS OR ACCURACY OF THE INFORMATION AND DATA HEREIN. INFORMATION IS SUPPLIED UPON THE CONDITION THAT THE PERSONS RECEIVING SAME WILL MAKE THEIR OWN DETERMINATION AS TO ITS SUITABILITY FOR THEIR PURPOSES PRIOR TO USE. HUNT FOREST PRODUCTS WILL NOT BE RESPONSIBLE FOR CLAIMS RELATING TO ANY PARTY'S USE OF OR RELIANCE ON INFORMATION AND DATA CONTAINED HEREIN REGARDLESS OF WHETHER IT IS CLAIMED THAT THE INFORMATION AND DATA ARE INACCURATE, INCOMPLETE, OR OTHERWISE MISLEADING.